

Data sheet

DF ibex



Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq\pm 0.02$		
Rated torque (Md _n)	Nm	1,000	2,000	3,000
Torque measuring system				
Technology	-	Rotating		
Rated torque (Md _n) #1	Nm	1,000	2,000	3,000
Rated torque short measurement range (optional, minimum) (Md _{ns}) #2	Nm	N/A		
Accuracy class extended (for Md _n)	%	N/A		
Outputs	-	Frequency (RS422), Voltage, CAN bus, Alert		
Test signal	-	see test report		
Mechanical dimensions #3				
Outer diameter of rotor #4	mm	158		
Lengths (Rotor, without centering)	mm	49		
Pitch circle diameter #5	mm	130.0		
Speeds and speed measuring systems				
Speed detection (integrated)	-	without		
Speed detection (optional)	-	magn.		
Maximum Speed without speed detection system	rpm	16,000		
Optional increased speed	rpm	18,000		
Maximum speed with magnetic speed encoder	rpm	9,000		
Maximum speed with optical speed encoder	rpm	N/A		
Maximum speed with inductive speed encoder	rpm	N/A		
Torque accuracy class per output type (related to Md _n)				
Frequency output	%	$\leq\pm 0.02$		
CAN output	%	$\leq\pm 0.02$		
Voltage output	%	$\leq\pm 0.04$		
Current output	%	N/A		
Frequency output (option higher accuracy)	%	N/A		
CAN (option higher accuracy)	%	N/A		

Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq \pm 0.02$		
Rated torque (Md _n)	Nm	1,000 2,000 3,000		
Linearity deviation including hysteresis related to Md _n #6				
Frequency, 0%...30%	%	$\leq \pm 0.010$		
Frequency, 30%...60%	%	$\leq \pm 0.015$		
Frequency, 60%...100%	%	$\leq \pm 0.020$		
CAN, 0%...30%	%	$\leq \pm 0.010$		
CAN, 30%...60%	%	$\leq \pm 0.015$		
CAN, 60%...100%	%	$\leq \pm 0.020$		
Voltage output	%	$\leq \pm 0.03$		
Current output	%	N/A		
Rel. standard deviation of the reproducibility according to DIN 1319, by reference to variation of the output signal (rel. to Md _n)				
Frequency output	%	$\leq \pm 0.006$		
CAN output	%	$\leq \pm 0.006$		
Voltage output	%	$\leq \pm 0.03$		
Current output	%	N/A		
Temperature influence per 10K in the nominal temperature range on the output signal related to the actual value of signal span (rel. to Md _n)				
Frequency output	%	$\leq \pm 0.02$		
CAN output	%	$\leq \pm 0.02$		
Voltage output	%	$\leq \pm 0.04$		
Current output	%	N/A		
Temperature influence per 10K in the nominal temperature range on the zero signal (rel. to Md _n)				
Frequency output	%	$\leq \pm 0.02$		
CAN output	%	$\leq \pm 0.02$		
Voltage output	%	$\leq \pm 0.04$		
Current output	%	N/A		
Long-term drift over 48h at reference temperature				
Voltage output	mV	$<1.5 / <3.0 / <0.8 / <1.5$		
Current output	μ A	N/A		

Technical data

Type	-	DF3 ibex		
Accuracy class	%	≤±0.02		
Rated torque (Md _n)	Nm	1,000 2,000 3,000		
Nominal sensitivity (range between zero torque and rated torque)				
Frequency output	kHz	5 / 20 / 30 / 120		
Voltage output	V	5.0 / 10.0 / 2.5 / 5.0		
Current output	mA	N/A		
Output signal at zero torque				
Frequency output	kHz	10 / 60 / 60 / 240		
Voltage output	V	0.0 / 0.0 / 2.5 / 5.0		
Current output	mA	N/A		
Nominal output signal				
Frequency output at positive nominal value	kHz	15 / 80 / 90 / 360		
Frequency output at negative nominal value	kHz	5 / 40 / 30 / 120		
Voltage output at positive nominal value	V	5 / 10 / 5 / 10		
Voltage output at negative nominal value	V	-5 / -10 / 0 / 0		
Current output at positive nominal value	mA	N/A		
Current output at negative nominal value	mA	N/A		
Max. modulation range				
Frequency output	kHz	0...420		
Voltage output	V	-12.0...12.0		
Current output	mA	N/A		
Group delay time (main TCU)				
Frequency output	μs	300		
Voltage output	μs	300		
CAN bus	μs	800		

Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq \pm 0.02$		
Rated torque (Md _n)	Nm	1,000	2,000	3,000

Speed measuring system	Inductive (track at rotor)			
Pulse per rev (PPR)	ppr.		N/A	
Maximum speeds (related to PPR)	rpm		N/A	
Max. output frequency (RS422)	kHz		N/A	
Minimum speed for sufficient pulse stability	rpm		N/A	
Speed measuring system	Magneto resistive (2 tracks approx. 90 degree phase shifted)			
Pulses per rev (PPR)	ppr.		1,000	
Maximum speeds (related to PPR)	rpm		9,000	
Max. output frequency (RS422)	kHz		150	
Minimum speed for sufficient pulse stability	rpm		>0.1	
Nominal clearance (sensor - pole ring)	mm		0.7	
Working airgap (sensor - pole ring)	mm		0.1...1.0	
Nominal axial displacement (rotor - stator) #7	mm		7.0	
Tolerance to nominal axial displacement (rotor - stator)	mm		± 0.5	
Speed measuring system	Optical			
Pulses per rev (PPR)	ppr.		N/A	
Maximum speeds (related to PPR)	rpm		N/A	
Max. output frequency (RS422)	kHz		N/A	
Minimum speed for sufficient pulse stability	rpm		N/A	
Nominal radial displacement (rotor - stator)	mm		N/A	
Tolerated radial displacement (rotor - stator) #7	mm		N/A	
Nominal axial displacement (rotor - stator) #7	mm		N/A	
Tolerance to nominal axial displacement (rotor - stator)	mm		N/A	

Technical data

Type	-	DF3 ibex		
Accuracy class	%	≤±0.02		
Rated torque (Md _n)	Nm	1,000	2,000	3,000

Angular measuring system

Requirement	-	Optional magnetic speed detection
Pulses per rev	ppr.	1,000
Resolution	°	0.090
Output signals	-	CAN bus, Voltage
Measurement ranges	°	0.00...360.00 / -180.00...180.00 / -360.00...360.00 / -720.00...720.00 / -1,080.00...1,080.00 / -1,440.00...1,440.00 / -1,800.00...1,800.00

Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq \pm 0.02$		
Rated torque (Md _n)	Nm	1,000	2,000	3,000
Temperature ranges				
Nominal temperature range (Rotor)	°C	0...80		
Operating temperature range (Rotor) #8	°C	-20...85		
Storage temperature range (Rotor)	°C	-30...85		
Nominal temperature range (Stator)	°C	0...80		
Operating temperature range (Stator) #9	°C	-20...85		
Storage temperature range (Stator)	°C	-30...85		
Nominal temperature range (TCU)	°C	0...70		
Operating temperature range (TCU)	°C	-20...70		
Storage temperature range (TCU)	°C	-30...85		
Mechanical shock (EN 60068-2-27)				
Quantity	-	1,000		
Duration	ms	3		
Acceleration	m/s ²	650		
Vibration load (EN 60068-2-6)				
Frequency	Hz	10...2,000		
Duration	min.	150		
Acceleration	m/s ²	200		
Load limits #10				
Limit torque, related to Md _n	%	350		
Breaking torque approx., related to Md _n	%	710	585	520
Axial limit force	kN	9.20	13.20	17.00
Lateral limit force	N	2,800.00	4,400.00	5,935.00
Bending limit torque	Nm	78.00	125.00	173.00

Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq \pm 0.02$		
Rated torque (Md _n)	Nm	1,000	2,000	3,000

Mechanical values				
Torsional stiffness	kNm/rad	828	1,342	1,778
Angle of twist at Md _n	°	0.069	0.085	0.097
Axial stiffness	kN/mm	231	331	425
Radial stiffness	kN/mm	186	293	395
Bending stiffness	kNm/°	2.50	4.00	5.50
Deflection at axial limit force	mm	<0.05		
Additional radial deviation at lateral limit force	mm	<0.02		
Parallel deviation at bending limit torque	mm	<0.09		
Inherent frequency	Hz	970	1,235	1,460
Balance quality-level (DIN ISO 1949)	-	G2.5		
Inertia of rotor	kgm ²	0.0092	0.0093	0.0093
Max. limits for relative shaft vibration (peak to peak) #11	µm	$S_{(p-p)} = \frac{9000}{\sqrt{n}}$		

Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq \pm 0.02$		
Rated torque (Md _n)	Nm	1,000	2,000	3,000
Weight approx.				
Rotor #12	kg	3.0	2.8	2.9
Stator (without speed encoder) #12	kg	1.04		
Mounting distances (without optional speed detection system)				
Nominal radial displacement (rotor - stator)	mm	164.5		
Tolerance to nominal radial displacement (rotor - stator)	mm	$+0.2/-0.2$		
Nominal axial displacement (rotor - stator) #7	mm	7.0		
Tolerance to nominal axial displacement (rotor - stator)	mm	$\leq \pm 0.5$		
Flatness and concentricity tolerances rotor				
Circular run-out-axial tolerance #13	mm	0.01		
Circular run-out-radial tolerance #13	mm	0.01		
Power supply				
Nominal supply	V	(DC) 24		
Supply range #14	V	(DC) 23...25		
Max. current consumption in measuring mode	A	<1		
Max. current consumption in start-up mode	A	<2		
Nominal power consumption	W	<24		
Load resistance				
Frequency output	-	RS422		
Voltage output	kOhm	≥ 50		
Dynamic				
Frequency output	kHz	≤ 6		
Voltage output	kHz	≤ 6		
Current output	kHz	N/A		
CAN output conversation rate	1/s	$\leq 2,000$		

Technical data

Type	-	DF3 ibex		
Accuracy class	%	$\leq \pm 0.02$		
Rated torque (Md _n)	Nm	1,000	2,000	3,000
Miscellaneous				
Protection class (Rotor)	-	IP54		
Protection class (Stator)	-	IP54		
Protection class (rotor, extended)	-	N/A		
Protection class (stator, extended)	-	N/A		
Pitch circle screw information	-	8 * M12 (10.9)	8 * M12 (10.9)	8 * M12 (12.9)
CAN bus type	-	2B		
Configuration interface	-	Ethernet		
Central hole	mm	N/A		
Material	-	Steel		
Measuring range (related to Md _n)	%	110		
Compatible evaluation units (TCU)	-	TCU5		
Stator type	-	DF3 ibex		
Sales information				
Article number	-	10008270		
U.S. FCC certificate	-	No		


Remarks and information

Link no.	Topic	Remark
#1	Nominal torque	Based on customer requests, the measurement systems can optionally be optimized for not listed nominal torque values (intermediate ranges possible).
#2	Second torque range	The written second nominal torque value ($M_{d_{ns}}$) is the smallest possible. Greater second torque ranges can be chosen on demand. Mechanical values and load limits vary between single and dual range torque meters. A data sheet for dual range torque meters with specific values can be requested.
#3	Dimensions	Mechanical dimensions are without engagement. Use the drawings and step files as master for your constructions.
#4	Details in the drawings	Value can vary by optional components. Please find details to this attribute in the integrated drawings.
#5	Pitch circle diameter	The pitch circle diameter is identically at input and output side for most systems. More information is given in the drawings of a product.
#6	Linearity	Values of Linearity deviation incl. Hysteresis can only be reached if positive and negative sensitivity values are used.
#7	Reference planes	Please check the drawings for information about the reference planes of this attribute.
#8	Temperature range (rotor)	No condensation allowed.
#9	Temperature range (stator)	No condensation allowed. Temperature related to housing ground point.
#10	Load limits	The given values are only valid if no other load occurs at the same time. If the loads in sum are 100%, the max. error will be 0.3% of the nominal torque. Limit and break torque are lower if other loads are applied (such as lateral forces).


Remarks and information

Link no.	Topic	Remark
#11	Vibration limits	Vibration limits are not an influence to the machine. They reflect the allowed effect onto the rotor (ISO 7919-3). Parameter "n" is given in "r/min.".
#12	Weights	Weights are related to components without options like speed detection system. Please contact us for exact weight information of options.
#13	Flatness and concentricity tolerances	The parameters of "Flatness and concentricity tolerances rotor" are manufacturing tolerances.
#14	Supply voltage	The supply voltage range must be given at measurement system side. Long wires can reduce the voltage level from power supply to measurement system.

Drawing




Drawing



©2026, ATESTEO GmbH & Co. KG, This product data sheet was created on 01.12.2026.

The information contained in the product data sheet corresponds to the status quo at the time the document was created. ATESTEO continually further develops its products and reserves the right to make changes to the technical data. ATESTEO does not accept any liability for consequential losses arising from the use of this product data sheet or the information contained therein.


Drawing



©2026, ATESTEO GmbH & Co. KG, This product data sheet was created on 01.12.2026.

The information contained in the product data sheet corresponds to the status quo at the time the document was created. ATESTEO continually further develops its products and reserves the right to make changes to the technical data. ATESTEO does not accept any liability for consequential losses arising from the use of this product data sheet or the information contained therein. 15


Drawing



DF3 ibex SPD_MGN System

DF3 ibex

Drawing



©2026, ATESTEO GmbH & Co. KG, This product data sheet was created on 01.12.2026.


The information contained in the product data sheet corresponds to the status quo at the time the document was created. ATESTEO continually further develops its products and reserves the right to make changes to the technical data. ATESTEO does not accept any liability for consequential losses arising from the use of this product data sheet or the information contained therein. 17

DF3 ibex SPD MGN

DF3 ibex

Rotor

Drawing




©2026, ATESTEO GmbH & Co. KG, This product data sheet was created on 01.12.2026.

The information contained in the product data sheet corresponds to the status quo at the time the document was created. ATESTEO continually further develops its products and reserves the right to make changes to the technical data. ATESTEO does not accept any liability for consequential losses arising from the use of this product data sheet or the information contained therein. 18

DF3 ibex SPD_MGN Stator

DF3 ibex


Drawing



©2026, ATESTEO GmbH & Co. KG, This product data sheet was created on 01.12.2026.

The information contained in the product data sheet corresponds to the status quo at the time the document was created. ATESTEO continually further develops its products and reserves the right to make changes to the technical data. ATESTEO does not accept any liability for consequential losses arising from the use of this product data sheet or the information contained therein. 19

Drawing



©2026, ATESTEO GmbH & Co. KG, This product data sheet was created on 01.12.2026.

The information contained in the product data sheet corresponds to the status quo at the time the document was created. ATESTEO continually further develops its products and reserves the right to make changes to the technical data. ATESTEO does not accept any liability for consequential losses arising from the use of this product data sheet or the information contained therein.

Would you like to learn more about our products, solutions, and services in the area of measuring systems, vehicle equipment, and actuators? Just call us at +49 (0) 2404 9870 570 or send email to equipment@atesteo.com. Your personal ATESTEO contact would be pleased to assist you.

ATESTEO GmbH & Co. KG
Konrad-Zuse-Straße 3
52477 Alsdorf
Germany

Phone +49 (0) 2404 9870 - 0
Email info@atesteo.com

<https://www.atesteo.com/en/>