



GAIN AND OFFSET ADJUSTMENTS SEALED (CODE 'Y')



IP67 SHORT CABLE GLAND - AXIAL (CODE 'Mxx')



ELECTRICAL OPTIONS/ SPECIFICATIONS

OUTPUT OPTION	OUTPUT	SUPPLY	
A	0.5 TO 4.5V RATIO METRIC	5V	STANDARD
B	±5V	±15V	
C	0.5 TO 9.5V	24V	
D	±10V	±15V	BUFFERED
G	0.5 TO 4.5V	24V	
	SUPPLY CURRENT 12mA TYP. 20mA MAX.		
F	4 TO 20mA 2-WIRE	24V	
H	4 TO 20mA 3-WIRE SINK	24V	
	4 TO 20mA 3-WIRE SOURCE	24V	

SINK VERSION OUTPUT COMPLIANCE 5-28V  
SOURCE VERSION DRIVE 300Ω MAX TO 0V  
CABLE: 0.2mm<sup>2</sup>, O/A SCREEN, PUR JACKET - SUPPLIED WITH 50cm OR REQUIRED LENGTH IN cm. e.g. 'L50'

3-CORE: JACKET Ø4mm  
4-CORE: JACKET Ø4.6mm  
CABLE/CONNECTOR\* CONNECTIONS;  
3 CORE 4 CORE CONNECTOR  
RED RED :1 +Ve  
BLACK GREEN :3 0V  
WHITE YELLOW :4 -Ve - OPTIONS: B OR D  
BLUE BLUE :2 OUTPUT  
SCREEN SCREEN :4 BODY - OPTIONS: A, C, E-H

\*CONNECTORS; MAXIMUM CONDUCTOR CROSS SECTION 0.75mm<sup>2</sup>  
RANGE OF DISPLACEMENT FROM 0-5° TO 0-15° e.g.12°, IN INCREMENTS OF 1°.

BODY MATERIAL:- STAINLESS STEEL.  
FLANGE BASE MATERIAL:- ALUMINIUM.  
SERVO MOUNT MATERIAL:- ALUMINIUM.

FURTHER OPTIONS:  
SPRING RETURN (CODE 'N') AVAILABLE UP TO ±50°  
CALIBRATED OUTPUT, PHYSICAL STOPS ±55°  
NOTE STANDARD DEVICE HAS NO STOPS.

D	ELEC. OPTIONS AMENDED.	PDM
E	FLANGE TH'KNNESS ADDED.	PDM
F	ADDITIONAL DIMS/VIEWS ADDED.	PDM
G	DISP. 5 TO 15° WAS 5 TO 20° RAN442	PDM
H	RANGE NOTE AMENDED - RAN1200	PDM



DRAWINGS NOT TO BE CHANGED WITHOUT REFERENCE TO THE CHANGE PROCEDURE.  
CHANGES TO PARTS USED IN INTRINSICALLY SAFE PRODUCT MUST BE APPROVED BY THE AUTHORISED PERSON  
THIS IS AN UNCONTROLLED PRINT AND WILL NOT BE UPDATED.



D	18/10/06		CHECKED BY	X	±0.4
E	05/01/10		RDS	X.X	±0.2
F	06/07/11			X.XX	±0.1
					DIMS mm
G	07/11/13	DESCRIPTION			
H	11/09/17	P502 RIPS SMALL ANGLE ROTARY SENSOR			
SCALE 10mm					
DRAWING NUMBER P502-11 REV H					
SHEET 1 OF 1					