TR3D Load Platform

Model LP-3030

- Measures forces and moments
- Three load ranges
- Universal mounting pattern
- · Environmentally protected
- Temperature compensated



Description

The *LP-3030 TR3D Load Platform* is a compact load platform designed to have higher force and moment capacity than individual load cells. The load platform uses four three-axis load cells to measure the net forces and moments acting on the platform. The load cells can be connected to the JB3 Junction Box, which combines the signals and outputs the net forces in three channels.

The load cells are made of high-grade stainless steel and have waterproof coatings, making them resistant to corrosion and harsh environmental conditions. Temperature compensation of the load cells ensures stable output throughout a wide temperature range.

The top plate has an array of tapped holes to which the user can attach equipment, test pieces, or machining fixtures. Custom platform sizes or mounting patterns can be designed upon request.

Specifications

	LP-3030-15	LP-3030-45	LP-3030-75
Maximum Force Capacity (per channel)	3,400 lb (15 kN)	10,000 lb (45 kN)	17,000 lb (75 kN)
Maximum Mx/My Moment Capacity	1,100 lb • ft (1.5 kN • m)	3,300 lb • ft (4.5 kN • m)	5,500 lb • ft (7.5 kN • m)
Maximum Mz Moment Capacity	1,800 lb • ft (2.5 kN • m)	5,500 lb • ft (7.5 kN • m)	8,900 lb • ft (12 kN • m)
Sensor (4 of each)	TR3D-A-1K	TR3D-A-3K	TR3D-A-5K
Full Scale Output, Nominal	3.3 mV/V		
Nonlinearity*	< 0.5 % of full scale		
Bridge Resistance, Nominal*	250 Ω		
Excitation Voltage, Maximum	10 Vdc or Vac rms		
Temperature Range, Compensated	75°F to 200°F (24°C to 93°C)		
Temperature Effect on Zero	< 0.2 % of full scale		
Temperature Range, Usable	-40 °F to 300 °F (-40 °C to 149 °C)		
Size (L x W x H)	15.8 x 11.8 x 4 in (400 x 300 x 100 mm)		
Weight	46 lb (21 kg)		
Standard Cable Length	10 ft (3.05 m) shielded		

*When used with junction box.

8500 Ance Road Charlevoix, MI 49720 Tel: 231-547-5511 Fax: 231-547-7070 01-5-22 Rev. A MICHIGAN SCIENTIFIC http://www.michsci.com corporation 321 East Huron Street Milford, MI 48381 Tel: 248-685-3939 Fax: 248-685-5406 This page is intentionally blank.

8500 Ance Road Charlevoix, MI 49720 Tel: 231-547-5511 Fax: 231-547-7070 01-5-22 Rev. A



321 East Huron Street Milford, MI 48381 Tel: 248-685-3939 Fax: 248-685-5406